

Linear.Lens.Profil

# New Generation

Peak performance

**REGIOLUX**  
Made in Germany

# SDG(V)L: New generation for peak performance

## New efficiencies in the light run


- up to 11 % more profit in efficiency
- NEW: Luminous efficiency up to 167 lm/W

DALI     IP 20

Service life











 50.000h  
L80/B10

Ta



## Lighting technologies for all applications

 A++

SDGLB	SDGLT	SDGLDA	SDGLK	SDGVL
wide-light distribution	narrow-light distribution	double asymmetrical light distribution	diffus light distribution	general diffuse
				
				



[www.regiolux.de](http://www.regiolux.de)

<http://www.regiolux.de/en/products/Quick-fit-mounting-system-Single-components/Device-mount-IP20/LED/>



Regiolux GmbH  
Hellinger Straße 3  
97486 Königsberg  
T +49 9525 89 0



Products								New	
Type	Unit	Lamps	P <sub>sys</sub> [W]	lm/W	ET Item no.	NL-B3 Item no.	DALI Item no.	lm	increase in efficiency
<i>LED - Linear.Lens.Profil direct wide distribution optically continuous IP 20</i>									
SDGLB	1500	LED 5000 840	31	166	1831 4304 100		1831 4306 600	+ 3%	+ 9%
		LED 6000 840	37	161	1831 4404 100	1831 4474 100	1831 4406 600	+ 4%	+ 10%
<i>LED - Linear.Lens.Profil direct narrow distribution optically continuous IP 20</i>									
SDGLT	1500	LED 5000 840	31	167	1832 4304 100		1832 4306 600	+ 3%	+ 9%
		LED 6000 840	37	162	1832 4404 100		1832 4406 600	+ 4%	+ 10%
<i>LED - Linear.Lens.Profil direct Batwing distribution optically continuous IP 20</i>									
SDGLDA	1500	LED 5000 840	31	166	1836 4304 100	1836 4374 100	1836 4306 600	+ 4%	+ 10%
		LED 6000 840	37	161	1836 4404 100		1836 4406 600	+ 5%	+ 11%
<i>LED - diffuser, frosted direct/indirect distribution optically continuous positioning variable IP 20</i>									
SDGLK	1500	LED 5000 840	31	158	1823 0304 100		1823 0306 600	+ 4%	+ 10%
		LED 6000 840	37	154	1823 0404 100	1823 0474 100	1823 0406 600	+ 4%	+ 11%
<i>LED - general diffuse optically continuous positioning variable IP 20</i>									
SDGVL	1500	LED 4500 840	31	150	1821 0304 150		1821 0306 650	+ 4%	+ 10%
		LED 5500 840	37	146	1821 0404 150		1821 0406 650	+ 5%	+ 11%