

maran

Moisture-proof lamp

Simple, flexible,
simply maran



REGIOLUX

Light control: netlife easy62

- Integrated RF motion sensor
- Easy adjustment via DIP switch
- Feed-through wiring retained via internal switching contact



Highlights

- Three adjustable colour temperatures (CCT3)
- Hygienic and safe according to HACCP standards
- Efficient lighting up to 153 lm/W
- Shock resistant with class IK08
- Dust-proof and spray-proof by IP65

Applications

Workshops & adjoining rooms
Food production areas
Car parks, garages
Storage rooms, hallways & staircases
Basement & laundry rooms

Housing:

- Housing made of polycarbonate
- Diffuser clips made of stainless steel
- Suspension lock as installation aid
- Feed-through wiring, 5-pole

Light technology:

- Opal diffuser, plastic PC
- Direct/indirect light distribution


Lamp:

- LED 50.000h L70B10, L80B50
- 840
- Adjustable light colour
- CCT3: 830/865 optional 845* (*SDCM6)

Control gear:

- Electronic multi-lumen driver
- DALI2 (luminaires suitable for IoT)

HF sensor detection range:



Type	Configuration	Colour	Control gear	LxBxH/DxH [mm]	Part number	lm/W	P _{sys} [W]
maran-DV/1200	LED 4800-3300 830/865	hg	EDM	1240 x 85 x 78	5013 2804 115	139-126	26-36
	LED 4800-3500 840	hg	EDM	1240 x 85 x 78	5013 2404 115	150-145	23-33
maran-DV/1500	LED 5800-3600 830/865	hg	EDM	1540 x 85 x 78	5013 5804 115	141-131	27-42
			EDM easy62	1540 x 85 x 78	5013 5854 115	141-131	27-42
	LED 6200 840	hg	DALI2	1540 x 85 x 78	5013 5406 615	146	43
	LED 6200-3900 840	hg	EDM	1540 x 85 x 78	5013 5404 115	153-146	26-43
			EDM easy62	1540 x 85 x 78	5013 5454 115	153-146	26-43
maran-DV/1200	LED 4800 840	hg	DALI2	1240 x 85 x 78	5013 2406 615	145	33

Mounting accessories	Type	Colour	Material	Details	Part number	
Mounting bracket	SBB	me	St	Bracket 0-90°, for the moisture-proof luminaires pirola, parga, maran; in packs of 2;	7998 0054 100	2



REGIOLUX

Regiolux GmbH
Hellinger Straße 3
D 97486 Königsberg
T +49 9525 89 0
info@regiolux.de
www.regiolux.de