

reloMP

Downlights

Side room
professionals



REGIOLUX

relo-MP



L80
B10
50.000h

830
840


IP44

Areas of application

- Rest areas and guest rooms
- Changing rooms, treatment rooms
- Foyers, lobbies
- Waiting areas
- Staircases, corridors

Highlights

- Universal IP44 downlight family for ceiling installation
- Micro-prismatic diffuser – standard-compliant
- Robust, die-cast housing
- Driver wired ready for operation
- Eligible implementation of refurbishments



RDES-MP/230 1900 lm

η_{LB} 100 %
lm/W 120
Direct/indirect 100/0 %
UGR q/l 22,3/22,3



Feed-through wiring: as always, quickly and without tools with DV-Box ET in the accessories

| relo-MP | Configuration | Colour | Control gear | DxH | Order number | lm/W | P _{sys} [W] | kg |
|------------------|---------------|--------|--------------------|----------|---------------|------|----------------------|-----|
| relo-RDES-MP/230 | LED 1900 830 | ws | ED | 230 x 59 | 3767 3114 170 | 116 | 16 | 1,2 |
| | LED 1900 840 | ws | ED | 230 x 59 | 3767 3104 170 | 120 | 16 | 1,2 |
| | LED 1900 830 | ws | DALI ¹⁾ | 230 x 59 | 3767 3116 670 | 116 | 16 | 1,2 |
| | LED 1900 840 | ws | DALI ¹⁾ | 230 x 59 | 3767 3106 670 | 120 | 16 | 1,2 |

| Accessories | Type | Colour | Material | Details | Order number | kg |
|---------------------|------------------|-------------|----------|-------------------------------------|---------------|----|
| Feed-through wiring | DV-BOX ET ET/ETM | sw RAL 9005 | Mix | DV-BOX ET/ ETM for relo | 7991 0001 100 | 1 |
| Ceiling attachment | RDES-AR 230 | vw RAL 9016 | St | Surface-mounting frame for relo 230 | 3767 9002 100 | 1 |

¹⁾Luminaires suitable for IoT (Internet of Things):